

# Performance<sup>®</sup> ALU-ZINC SPRAY #53

BRIGHT COLORED ZINC PROTECTION COATING SPRAY

**Product Code**  
267800301  
Industrial Sprayscans



PAINT

## Bright Colored Zinc Protection Coating Spray

This product is a high quality Alu-Zinc spray to treat galvanized and untreated steel. Performance Alu-Zinc Spray is used as a rust and corrosion protection on iron and steel surfaces.

Performance Alu-Zinc spray can be used for repair of damaged galvanic surfaces, protection of exhaust systems and protection of welding seams.

### Benefits:

- Resistant to petrol, chemicals and weather influences
- Outstanding cathodic corrosion prevention
- Excellent adhesion
- Good filling properties
- Lighter color because of the aluminum component in this formula
- Spot-weldable
- Resists temperatures up to 250°C



e 400ml

### Typical Performance Data

| Property                 | Value        |
|--------------------------|--------------|
| Base                     | Epoxy-Ester  |
| Colour                   | Silver-Grey  |
| VOC, % w/w               | 76           |
| Solid content, % w/w     | 24           |
| Coverage, m <sub>2</sub> | 1.25 to 1.75 |
| Dust dry                 | 10 to 15 min |
| Tack free                | 20 to 30 min |
| Hardened/Re-sprayable    | >24h         |
| Heat resistant           | Up to 250°C  |

### How to use:

The surface should be clean, dry and free of grease and oil. The aerosol should have room temperature. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter. Apply the Alu-Zinc spray in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

All performance data on this Technical Data Sheet are indicative only and can vary during production.